

EMIG/STICK Series



The MIG/STICK Series welders range from 200 - 250amp and produce extremely smooth current. Featuring both Mig and Stick functions they are a compact trolley configuration with the ability to run 0.6 - 1.2mm wire through the 4 roller drive system. They have the capacity to exceed the demands of any high performing workshop.

- New Generation advanced IGBT
- Inverter Technology
- Multi Process with MIG (GMAW) and MMA (SMAW)
- Stepless wire feeding speed, voltage and inductance adjustment knob for MMA welding
- Welding mode 2T/4T selection switch
- Easy welding cable connections with European type quick connectors
- Fan cooling system
- IP21S Protection class
- Equipped with voltage and thermal protection

TECHNICAL DATA:	EMIG 201 III	EMIG 251 III
Input Power (V)	230	230
Rated Input Current I _{eff} ' (A)	17.9	17.9
Max Input Current (A)	37	43
Rated Input Capacity (kVA)	8.51	9.9
Open Circuit Voltage(V)	75	74
Welding Current Range (A)	MIG 30-200 STICK 10-200	MIG 30-250 STICK 30-200
Duty Cycle (A)	60% @ 200	60% @ 250
Weight (KG)	50	52
Wire Feed (mm)	0.8 - 1.2	0.8 - 1.2
Electrode Size (mm)	1.6 - 4.0	1.6 - 4.0
Mig Gun	MB24	MB24



ACCESSORIES:



Mig Gun - 4m



Earth Clamp
and Cable - 3m



Gas Hose - 4m



Contact Tips

